

Product	LuxeWall® FlameGuard® Fire Rated System
Product Description	LuxeWall® FlameGuard® Fire Rated System is a fire rated architectural boundary wall system tested and approved for both FRL 60/60/60 and FRL 90/90/90 for use in commercial and residential applications. LuxeWall® FlameGuard® is a lightweight, conceal fixed and architecturally finished high performance wall product that simplifies installation on zero boundary properties where site access is difficult.
Supplier	BONDOR
Contact Number	1300 300 099
Website	www.bondor.com.au

Product Overview

Core	MW (Mineral Wool)
Width (cover mm)	1200, 900^
Thickness (mm)	50, 75 (other thicknesses available on request)
Length	Up to 6.5m (check for availability)
External Material	BlueScope® COLORBOND® Steel 0.6mm G300
External Finishes	Plain (Other options available)^
Exterior Colour Options	Standard, Matt & Metallic COLORBOND® options available
Internal Material	BlueScope® COLORBOND® Steel 0.6mm G300 with HygienePlus®
Internal Finishes	Plain
Interior Colour Options	Surfmist
Paint System	AS/NZS 2728 & AS 1397
Accreditations	Codemark Certificate Number CM40239
Acoustic Properties	Rw 40, 45 *depending on construction
Material Group Numbers	C1.10 Group 1
Bushfire Attack Level	BAL-FZ (All exposed core to be covered with flashing)

Technical Properties

Thermal - AS/NZS 4859.1

Total R-Value (m²K/W)	50, 75mm LuxeWall® FlameGuard® delivers Total R-value of 1.9, 2.6 for insulation average temperature of 15 °C. Contact us for other temperatures and construction methods.
---	--

Acoustics - AS 1191, AS/NZS 1276 & AS/NZS ISO 717.1

R_w Value (dB)	LuxeWall® FlameGuard® has been tested in accordance with the requirements of AS 1191. The Weighted Sound Reduction Index (R _w) of the panel is calculated using AS/NZS 1276 and AS/NZS ISO 717.1 respectively with acoustic values of Rw 40 or 45 (with insulation between studs). Refer to Bondor® Australia for your specific application.
---------------------------------	--

Fire

Combustibility	AS 1530.1 Non-combustible
Fire hazard properties	AS/NZS 1530.3
Ignitability Index	0
Spread of Flame Index	0
Heat Evolved Index	0
Smoke Index	3
SMOGR_{RC}	< 100
Fire Resistance	AS 1530.4 FRL 90/90/90

Material Group Numbers AS 5637.1 / AS ISO 9705	LuxeWall® FlameGuard® MW steel skinned insulated building panels conform to the requirements of the BCA Specification C1.10 as Group 1. Group 1 - Panel up to 150mm thick with steel 'wall-wall' and 'wall-ceiling' angles fixed with steel rivets or screws at 300mm centres is classified as Group 1.
---	--

Bushfire Attack Level AS 3959	LuxeWall® FlameGuard® is suitable for use as external walls of Class 1 and 10 buildings to be constructed in designated bushfire prone areas that have a BAL-FZ or less.
--------------------------------------	--

Structural - AS/NZS 1170, AS 1562.1, AS4040

Span Tables Bondor® provides the latest Ultimate Limit State Span Tables developed specifically for Australasian conditions, in accordance with AS/NZS 1170, AS 1562.1 & AS 4040. Refer to Span Tables for detailed design guidelines and Span Tables for Non-Cyclonic Regions A & B. Refer to Span Table Notes for design guidelines relating to fixing, and deflection limits. The panel design shall be specified by the certifying engineer as determined from the Span Tables.

Support Details The support spacing shall be specified by the structural engineer as determined from the Span Tables.

Safe Handling & Installation

Panel Length Up to 16m, however site, transport and wind load restrictions can limit panel length.

Storage Panels should always be kept dry and if placed on site, stored off the ground, slightly inclined, allowing adequate drainage and ventilation of the panel pack. No other materials to be stored / stacked on top of panel pack.

Handling In the event of manual handling, careful consideration should be given to panel weight and appropriate PPE. Consider using mechanical aides if necessary.

Safety The contractor is to determine and use safe working methods throughout the installation and construction period, which complies with OHS requirements. A safe work method template (although NOT project specific) is available from Bondor®.

Supporting Frame The builder is to ensure that the substrates including slabs and kerbs; and sub frames are straight, smooth and fit for purpose.

Fixing Fixings are to meet the requirements of BlueScope TB-16 Fasteners for Roofing and Walling Product Selection Guide. Fasteners must be manufactured from high grade carbon steel with a minimum class 4 anti-corrosion coating as per Australian Standards. Refer to Span Tables Notes for design guide relating to screw fixing and IPCA for cold storage compliance.

Flashing Flashings are manufactured from 0.55mm BlueScope COLORBOND® steel and installed to AS 1562.1 or as otherwise specified in the Bondor® Cold Storage or Cladding Construction Drawings. Aluminium can be used if there is no Group Number requirement.

Sealant Sealant to be neutral cure and meet recommendations for sealants as per BlueScope TB-9 Sealants for Exterior Finishes. Silicon, polyurethane, butyl mastic and acrylic based sealants may be appropriate if neutral cure and recommended by their manufacturer for use on COLORBOND® steel and for the application. Sealant to be placed between flashings/angles and panel and between panel joints as shown on the Bondor® Standard Construction Details.

Installation Installation as per the Bondor® Standard Construction Details.

- Panels are to be cut & trimmed to ensure a flush finish.
- Panels are to be confirmed square & plumb as per project requirements.
- Panels are to be cut with a suitable metal cutting circular type saw. Angle grinder is not recommended.
- Penetrations for outlets, vents, flues etc. are to be flashed & sealed with appropriate materials. Refer flashing details above.
- Gaps to be filled with a suitable sealant or foam filler.
- Refer to Bondor® Standard Construction Details & Fixing Details above for fastener requirements.
- Remove all swarf and any foreign matter immediately from all panel surfaces as per BlueScope TB-5 Swarf staining of steel profiles.

Maintenance Refer to BlueScope TB-4 Maintenance of COLORBOND® and Zinalume® Steel and the relevant Bondor® maintenance information.

Warranties & Disclaimers

Warranty Bondor® offer a conditional warranty up to 15 years on LuxeWall® FlameGuard® for use as architectural wall panels from install date for projects on an application basis, dependent on project location, design, installation, end use, environmental conditions and maintenance of the product. Please contact Bondor® sales team with your specific project details for more information on the available conditional warranties.

Disclaimers Under certain light conditions this product may show an undulating surface which can vary depending on exterior profile and steel gauge selection as well as the environments varying light conditions.